



iNPIPE PRODUCTS™ Foam Pig Data Sheet






iNPIPE PRODUCTS™ manufacture a comprehensive range of foam pigging products which are designed for a variety of pipeline pigging applications including:

Proving Swabbing Drying Wiping De-watering Scraping

Product Removal Debris Removal

Cleaning

Aggressive Cleaning



Features:

- Available in 4 standard densities of foam, Low Density (1.5-2lb/Cu.ft), Medium Density (5-7lb/Cu.ft), Heavy Density (8-10lb/Cu.ft) and Extra Heavy (20lb/Cu.ft)
- The range includes a number of different finishes designed for specific applications. These include Bare Foam, Fully Coated, Criss Cross, Silicone Carbide and both Wire & Nylon Brush designs
- Foam pigs can be adapted to include transmitter cavities ,tow loops, gauge plates and encapsulated magnets for tracking
- Dual densities are available on request
- Sizes ranging from 1/2" to 74"

Benefits:

- Maintenance free, disposable product
- Capable of travelling long distances
- Can be customised to meet client requirements
- Can reduce through a pipeline by up to 50% in diameter
- Capable of negotiating short radius 90° bends and elbows
- Able to traverse bends, mitres, tees and various valve configurations
- Can be used on pipelines not originally designed for pigging activities

Standard Foam Dimensions

Nominal Size	A	В	С				
2	58	86	113				
3	82	117	149				
4	108	163	205				
6	159	240	304				
8	212	318	402				
10	266	375	450				
12	318	460	580				
14	350	550	695				
16	403	605	750				
18	454	680	850				
20	504	752	950				
22	552	818	1028				
24	609	912	1140				
26	660	1000	1260				
28	707	1062	1334				
30	765	1145	1423				
32	810	1229	1546				
34	850	1260	1586				
36	909	1370	1710				
38	970	1435	1795				
40	1020	1515	1895				
42	1066	1600	2005				
44	1100	1600	2005				
46	1225	1825	2286				
48	1237	1780	2250				

A comprehensive range of additional moulds are available to suit client specific pipe schedules. Dimensions are approximations in mm.

International Pipeline Products Ltd, Gatherley Road, Brompton on Swale, Richmond, North Yorkshire, England, DL10 7JH Tel: +44 (0)1748 813270 Fax: +44 (0)1748 813454 - E-mail: expsales@inpipeproducts.co.uk - uksales@inpipeproducts.co.uk Registered in England 1852899















Foam Pig Selection Matrix:

Pig Categories	Appearance		Types	Density	Proving	Swabbing	Drying	Wiping	De-Watering	Scraping	Product Remons	Debris Remo	Cleaning	Aggressive
Low Density Pigs		SF-B	Soft Foam - Bare (With or without Sealing Disc)	1-5 -2lb/Cu.ft	1	✓	1							
		SF-FC	Soft Foam- Fully Coated	1-5 -2lb/Cu.ft		1		1	1		1			
		SF-XX	Soft Foam - Criss Cross (P.U. Coating)	1-5 -2lb/Cu.ft		1		1	1					
		SF-SC	Soft Foam - Silicone Carbide	1-5 -2lb/Cu.ft						1			1	
Medium Density Pigs		LRSD-BF	Long Run Standard Duty - Bare Foam (With or without Sealing Disc)	5-7lb/Cu.ft		1	V	1	1		1	√		
		LRSD-FC	Long Run Standard Duty - Fully Coated	5-7lb/Cu.ft		1		1	1		1		1	
	NA	LRSD-XX	Long Run Standard Duty - Criss Cross (P.U. Coating)	5-7lb/Cu.ft		1		1	1		~	1	V	
		LRSD-SC	Long Run Standard Duty - Silicone Carbide	5-7lb/Cu.ft						V			1	
		LRSD-WB	Long Run Standard Duty - Wire Brush	5-7lb/Cu.ft						1			1	
Pigs		LRHD-BF	Long Run Heavy Duty - Bare Foam (With or without Sealing Disc)	8-10lb/Cu.ft		√	✓	✓	1		✓	1		
		LRHD-FC	Long Run Heavy Duty - Fully Coated	8-10lb/Cu.ft		√		✓	1		1		1	
		LRHD-XX	Long Run Heavy Duty - Criss Cross (P.U. Coating)	8-10lb/Cu.ft		1		1	1		1	1	1	
		LRHD-SC	Long Run Heavy Duty - Silicone Carbide	8-10lb/Cu.ft						√				1
		LRHD-WB	Long Run Heavy Duty - Wire Brush	8-10lb/Cu.ft						1				1
Extra Heavy Density Pigs		LR-EXHD	Long Run Extra Heavy Duty	20lb/Cu.ft		✓	√	✓	1	✓	√	✓	√	

Pig Application Key:

- Proving: Ensuring that pig travels from one end of pipeline to the other
- Swabbing: Removing moisture from pipeline until dry
- Drying: Initial drying of pipeline prior to air drying and vacuum drying
- Wiping: Removal of small particles/debris from pipe wall
- De-Watering: Removing water from pipeline
- Scraping: Abrasive cleaning of the pipeline
- Product Removal: Removal of product from pipeline
- Debris Removal: Removing debris from pipeline

International Pipeline Products Ltd, Gatherley Road, Brompton on Swale, Richmond, North Yorkshire, England, DL10 7JH Tel: +44 (0)1748 813270 Fax: +44 (0)1748 813454 - E-mail: expsales@inpipeproducts.co.uk - uksales@inpipeproducts.co.uk Registered in England 1852899


















Foam Pig Extras:


In conjunction with the standard range of foam pigs **iNPIPE PRODUCTS**TM also offer a large range of special pig options to cater for a wide range of pigging applications:














Foam Pig Selection Example:

Purpose:	Cleaning (Debris Removal)
Pipeline Size & Length:	20" x 30km
Wall Thickness:	15.09-26.19mm (Sch 40- Sch 80)
Pipeline Material:	API 5L Gr x 60. C.Steel w/internal epoxy coating
Barred Tees:	Yes
Additional Requirements:	Front pulling/handling rope required
	EM transmitter cavity required

Solution:

- Long run standard duty foam (LRSD)
- Cleaning in epoxy coated line (NFB)
- Front pulling/handling rope (PF-F)
- Transmitter cavity (TF-T)



REF: 20" LRSD-NFB-PF-F-TF-T

International Pipeline Products Ltd, Gatherley Road, Brompton on Swale, Richmond, North Yorkshire, England, DL10 7JH Tel: +44 (0)1748 813270 Fax: +44 (0)1748 813454 - E-mail: expsales@inpipeproducts.co.uk - uksales@inpipeproducts.co.uk Registered in England 1852899















Client Reference List:



















































